

Photo Paper Technical Data Sheet



120g Double Sided Satin Paper

General Description

- Satin finish Coated, Double Sided high resolution paper for brochures, booklets, letters, graphics etc
- Coated on both sides with high resolution coating for inkjet
- Free of any logo or watermark on the reverse
- Further uses include calendar making, menus, presentations, charts and enlargements

Technical Data

Parameter	Value	Unit	Standard
Weight	130 ± 10	g/m ²	ISO536
Paper Thickness	210 ± 15	µm	ISO534
Opacity	97 ± 3	%	ISO2471
Stiffness MD		mN	ISO2493
Stiffness CD		mN	ISO2493
Gloss value 60° (fs)	20	-	
Smoothness (fs)	100 ± 40	sec	ISO5627
CIE Whiteness (fs)	100		ISO11475
Shade (D65/10°) (fs) L*			ISO5631-2
a*			ISO5631-2
b*			ISO5631-2

Availability

A4, A3

Compatibility

All Inkjet Printers. Should not be used on laser printers.

Additional Information

Best printing results achieved in a standard climate of 23°C and 50% relative humidity. For problem-free running, always store the product in original packaging and protect it from direct sunlight and moisture. Before using our medium, check its suitability on your printer and for your planned application. We can assume no liability resulting from technical changes in printers and/or inks. Changes in the product design due to technical further developments will not be announced in advance

Photo Paper Direct Ltd.
Unit 8, Shakespeare Industrial Estate, Watford, WD24 5RR
T: +44 (0)1923 232 590 E: sales@photopaperdirect.com

Web: www.photopaperdirect.com
Facebook: [facebook.com/PhotoPaperDirectUK](https://www.facebook.com/PhotoPaperDirectUK) Twitter: twitter.com/PhotoPaper
Google: plus.google.com/+photopaperdirect/